

TECHNICAL INFORMATION**FLOOR COATINGS****WATER-BORNE**

Type	Chemistry	Product	Benefits
Primers 1C	Styrene Acrylic	FLOOR PRIMER AQUA COLOURLESS	Excellent adherence to mineral substrates (ceramic, cement, etc.) y high water resistance.
	Acrylic	HIGH ADHERENCE PRIMER	Water based primer for all surfaces to improve the adherence of upper coatings on glass, tiles, vitrified terrazzo, PVC, metals, and some kind of plastics...
Primers 2C	Epoxy	DECO-EPOXI AQUA COLOURLESS	Two components water based epoxy primer for protection of mineral substrates. It improves the adherence of upper coats.
	PU-Acrylic	DECOPUR AQUA COLOURLESS	Special acrylic polyol for polyurethane systems of two components. Long durability, resistant to abrasion and chemicals Applications: Commercial/professional transport, machinery and wood.
Concrete Coatings			
Topcoats 1C	Styrene Acrylic	SPORTS LINE	High resistance to abrasion. High Adherence to mineral substrates.
	Acrylic	DECO-FLOORS AQUA	High resistance to abrasion. Long outdoors durability, high resistance to chemicals, oil, petrol, diesel, etc.
Topcoats 2C	Epoxy	DECO-EPOXI AQUA	Two components water based epoxy for protection of mineral substrates. Excellent chemical and mechanical resistance.
	PU-Acrylic	DECOPUR AQUA	Special acrylic polyol for polyurethane systems of two components. Long durability, resistant to abrasion and chemicals Applications: Commercial/professional transport, machinery and wood.
Type	Chemistry	Product	Benefits
Primers 1C	Acrylic	VARNISH INTERIOR AQUA	Nano-polymer varnish specially developed for wood floors, furniture and doors.

Pinturas Decolor

Polígono Industrial El Salvador Avenida 3ª, Parcela 4 y 5

Apdo. 106 – 02630 La Roda (Albacete) Spain

Teléfono: +34 967 44 17 14

Fax: +34 967 44 33 54

E-mail: dptotecnico@decolor.com<http://www.decolor.com>

TECHNICAL INFORMATION**FLOOR COATINGS**

	Acrylic	PROTECTIVE SEALER AQUA	With very small resin particles that provide a good penetration into the substrate.
	Acrylic	HIGH ADHERENCE PRIMER	High resistance to woodknots secretions. Good stain blocking on tropical woods. Suitable for interior and exterior applications.
Primers 2C	PU-Acrylic	DECOPUR AQUA COLOURLESS	Special acrylic polyol for polyurethane systems of two components. Long durability, resistant to abrasion and chemicals Applications: Commercial/professional transport, machinery and wood.
Wood Coatings			
Topcoats 1C	Acrylic	VARNISH INTERIOR AQUA	Nano-polymer varnish specially developed for wood floors, furniture and doors.
	Acrylic	DECO-FLOORS AQUA	High resistance to abrasion. Long durability in exterior environments .High resistance to chemicals, oil, petrol, diesel, etc.
	PU-Alkyd	ALBORLAC AQUA	Very good drying properties and good resistance to weathering and yellowing. Suitable for doors, furniture, floors...
Topcoats 2C	PU-Acrylic	DECOPUR AQUA	Special acrylic polyol for polyurethane systems of two components. Long durability, resistant to abrasion and chemicals Applications: Commercial/professional transport, machinery and wood.

Abbreviations:

PU: polyurethane

1K: one component

2K: two component

PINTURAS
DECOLOR[®]

Pinturas Decolor

Polígono Industrial El Salvador Avenida 3ª, Parcela 4 y 5

Apdo. 106 – 02630 La Roda (Albacete) Spain

Teléfono: +34 967 44 17 14

Fax: +34 967 44 33 54

E-mail: dptotecnico@decolor.com<http://www.decolor.com>

TECHNICAL INFORMATION**FLOOR COATINGS****SOLVENT-BORNE**

Type	Chemistry	Product	Benefits
Primers 1C	Acrylic	DECOFIX	With very small resin particles that provide a good penetration and consolidation in the substrate.
	Ester epoxy	POLYVALENT PRIMER	High adherence. Resistant to abrasion and chemical substances.
Primers 2C	Epoxy	EPOXI PRIMER 2K LD	Two components water-based epoxy for protection of mineral substrates. To improve the adherence of upper coatings
Concrete Coatings			
Topcoats 1C	Acrylic	FLOOR ACRYLIC COATING	High resistance to abrasion and long outdoors durability. High resistance to chemicals, oil, petrol, diesel, etc...
	Ester epoxy	POLYVALENT PRIMER	High adherence. Resistant to abrasion and chemical substances.
	Acrylic	FLOOR VARNISH	High resistance to abrasion, long outdoor durability. High resistance to chemicals, oil, petrol, diesel, etc...
	Acrylic	TRAFFIC MARKING COATING	Resistance to abrasion, High Adherence to mineral substrates.
Topcoats 2C	Epoxy	DECO-EPOXI 2K LD	Two components epoxy paint for protection of mineral substrates. Excellent chemical and mechanical resistance.

Type	Chemistry	Product	Benefits
Primers 1C	PU-Alkyd	MARINE VARNISH	Long durability. Blocking resistance. With UV filter.
Wood Coatings			
Topcoats 1C	PU-Alkyd	MARINE VARNISH	Long durability. Blocking resistance. With UV filter.

Abbreviations:
PU: polyurethane
1K: one component
2K: two component

Pinturas Decolor

Polígono Industrial El Salvador Avenida 3ª, Parcela 4 y 5
Apdo. 106 – 02630 La Roda (Albacete) Spain
Teléfono: +34 967 44 17 14 Fax: +34 967 44 33 54
E-mail: dptotecnico@decolor.com <http://www.decolor.com>