

**TECHNICAL INFORMATION****WOOD COATINGS****WATER-BORNE**

Type	Chemistry	Product	Benefits
<b>Primers 1K</b>	Alkyd	<b>SEALER AQUA</b>	High resistance to woodknots secretions, Easily sandable sealer. Suitable for interior and exterior applications.
	Acrylic	<b>HIGH ADHERENCE PRIMER</b>	High resistance to woodknots secretions. Good stain blocking on tropical woods. Suitable for interior and exterior applications.
	Acrylic	<b>PROTECTIVE SEALER AQUA</b>	With very small resin particles that provide a good penetration on the substrate.
	Acrylic	<b>LASUR AQUA</b>	Long durability. Resistance to blocking. With UV filter.
<b>Primers 2K</b>	PU-Acrylic	<b>DECOPUR AQUA COLORLESS</b>	Special acrylic polyol for polyurethane systems of two components. Long durability, resistant to abrasion and to chemicals Applications: Comercial/professional transports, machinery and wood.
<b>Wood Coatings</b>			
<b>Topcoats 1K</b>	Acrylic	<b>LASUR AQUA</b>	Long durability, Resistance to blocking. It lets the grain stand out. With UV filter.
	Acrylic	<b>VARNISH INTERIOR AQUA</b>	Nano-polymer varnish specially developed for Wood floors, furniture and doors.
	Acrylic	<b>VARNISH AQUA</b>	Long durability, blocking resistance. With UV filter.
	Alkyd	<b>ALBOR AQUA</b>	Hybrid technology, alkyd performance, High brightness, hydrophobic and durable, low yellowing tendency.
	Alkyd-PU	<b>ALBORLAC AQUA</b>	Very good drying properties and good resistance to weathering and yellowing. Good adherence on metal and plastic substrates. Suitable for agricultural machinery, doors, furniture, etc.
<b>Topcoats 2K</b>	PU-Acrylic	<b>DECOPUR AQUA</b>	Special acrylic polyol for polyurethane systems of two components. Long durability, resistant to abrasion and chemicals Applications: Comercial/professional transport, machinery and wood.

Abbreviations:

**Pinturas Decolor**

Polígono Industrial El Salvador Avenida 3ª, Parcela 4 y 5

Apdo. 106 – 02630 La Roda (Albacete) Spain

Teléfono: +34 967 44 17 14

Fax: +34 967 44 33 54

E-mail: [dptotecnico@decolor.com](mailto:dptotecnico@decolor.com)<http://www.decolor.com>



## TECHNICAL INFORMATION

### WOOD COATINGS

PU: polyurethane  
1K: one component  
2K: two component



PINTURAS  
DECOLOR®

#### **Pinturas Decolor**

Polígono Industrial El Salvador Avenida 3ª, Parcela 4 y 5  
Apdo. 106 – 02630 La Roda (Albacete) Spain  
Teléfono: +34 967 44 17 14 Fax: +34 967 44 33 54  
E-mail: [dptotecnico@decolor.com](mailto:dptotecnico@decolor.com) <http://www.decolor.com>

**TECHNICAL INFORMATION****WOOD COATINGS****SOLVENT-BORNE**

Type	Chemistry	Product	Benefits
<b>Primers 1K</b>	Alkyd	<b>PROTECTIVE SEALER</b>	With very small resin particles that provide a good penetration on the substrate.
	Alkyd	<b>LASUR</b>	Long durability, blocking resistance With UV filter.
	Alkyd	<b>SEALER</b>	High resistance to woodknots secretions. Good stain blocking on tropical woods. Suitable for interior and exterior applications
<b>Wood Coatings</b>	Alkyd	<b>VARNISH GLOSS-SATIN-MATT</b>	Long durability. Resistance to blocking, carácter universal para acabados.
		<b>LASUR</b>	Long durability, Resistance to blocking It lets the grain stand out. With UV filter.
	Alkyd-PU	<b>MARINE VARNISH</b>	Long durability, blocking resistance, With UV filter.
	Alkyd-PU	<b>ALBOR GLOSS</b>	Hybrid technology, alkyd with aliphatic PU, High brightness, hydrophobic and durable, low yellowing tendency.
	Alkyd-PU	<b>ALBOR SATIN</b>	Hybrid technology, alkyd with aliphatic PU, medium brightness, hydrophobic and durable, low yellowing tendency.
	Alkyd-PU	<b>ALBOR MATT</b>	Hybrid technology, alkyd with aliphatic PU, low brightness, hydrophobic and durable, low yellowing tendency.

Abbreviations:

PU: polyurethane

1K: one component

2K: two component

PINTURAS  
**DECOLOR**<sup>®</sup>

**Pinturas Decolor**

Polígono Industrial El Salvador Avenida 3ª, Parcela 4 y 5

Apdo. 106 – 02630 La Roda (Albacete) Spain

Teléfono: +34 967 44 17 14

Fax: +34 967 44 33 54

E-mail: [dptotecnico@decolor.com](mailto:dptotecnico@decolor.com)<http://www.decolor.com>