

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 23451-DECO-EPOXI 2C AGENTE CURADO 234 (B)



Version: 2  
Revision date: 12/06/2018

Page 1 of 12  
Print date: 12/06/2018

### SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

#### 1.1 Product identifier.

Product Name: DECO-EPOXI 2C AGENTE CURADO 234 (B)  
Product Code: 23451

#### 1.2 Relevant identified uses of the mixture and uses advised against.

The solvent coating for indoor use.

#### Uses advised against:

Uses other than those recommended.

#### 1.3 Details of the supplier of the safety data sheet.

Company: **PINTURAS DECOLOR, S.L.**  
Address: POL. INDUSTRIAL EL SALVADOR, AVENIDA 3ª, PARCELAS 4-5  
City: 02630 - LA RODA  
Province: ALBACETE - ESPAÑA  
Telephone: +34 967 44 17 14  
Fax: +34 967 44 33 54  
E-mail: decolor@decolor.com  
Web: www.decolor.com

**1.4 Emergency telephone number:** +34 967 44 17 14 (Only available during office hours; Monday-Friday; 09:00-19:00)

### SECTION 2: HAZARDS IDENTIFICATION.

#### 2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008:

- Eye Dam. 1 : Causes serious eye damage.
- Flam. Liq. 3 : Flammable liquid and vapour.
- Skin Irrit. 2 : Causes skin irritation.
- Skin Sens. 1 : May cause an allergic skin reaction.

#### 2.2 Label elements.

##### Labelling in accordance with Regulation (EU) No 1272/2008:

##### Pictograms:



Signal Word:

**Danger**

H statements:

- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.

P statements:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 23451-DECO-EPOXI 2C AGENTE CURADO 234 (B)



Version: 2  
Revision date: 12/06/2018

Page 2 of 12  
Print date: 12/06/2018

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER/doctor/...  
P321 Specific treatment (see ... on this label).  
P370+P378 In case of fire: Use multipurpose powder extinguisher. (ABC) to extinguish it.

Contains:  
n-butanol, butan-1-ol  
amides, from C-18-unsatd. Fatty acid dimers, tall oil fatty acids and triethylenetetramine, reaction products with bisphenol A-epychloridrine polymer.

### 2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

### 3.1 Substances.

Not Applicable.

### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
CAS No: 68953-09-3	amides, from C-18-unsatd. Fatty acid dimers, tall oil fatty acids and triethylenetetramine, reaction products with bisphenol A-epychloridrine polymer.	10 - 50 %	Eye Irrit. 2, H319 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-
Index No: 601022009 CAS No: 1330-20-7 EC No: 215-535-7 Registration No: 012119488216-32	[1] xylene	10 - 50 %	Acute Tox. 4, H312 - Asp. Tox. 1, H304 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315	-
Index No: 603-004-00-6 CAS No: 71-36-3 EC No: 200-751-6 Registration No: 01-2119484630-38-XXXX	[1] n-butanol, butan-1-ol	10 - 20 %	Acute Tox. 4 *, H302 - Eye Dam. 1, H318 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315 - STOT SE 3, H335 - STOT SE 3, H336	-
Index No: 601-023-00-4 CAS No: 100-41-4 EC No: 202-849-4 Registration No: 01-2119489370-35-XXXX	[1] ethylbenzene	1 - 10 %	Acute Tox. 4 *, H332 - Asp. Tox. 1, H304 - Flam. Liq. 2, H225 - STOT RE 2, H373(órganos de audición)	-

(\*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

\* See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a Community workplace exposure limit (see section 8.1).

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 23451-DECO-EPOXI 2C AGENTE CURADO 234 (B)



Version: 2  
Revision date: 12/06/2018

Page 3 of 12  
Print date: 12/06/2018

### SECTION 4: FIRST AID MEASURES.

**IRRITANT PREPARATION.** Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

#### **4.1 Description of first aid measures.**

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

#### **Inhalation.**

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

#### **Eye contact.**

Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Don't let the person to rub the affected eye.

#### **Skin contact.**

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

#### **Ingestion.**

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

#### **4.2 Most important symptoms and effects, both acute and delayed.**

Corrosive Product, contact with eyes or skin can cause burns; ingestion or inhalation can cause internal damage, if this occurs immediate medical assistance is required.

Contact with eyes may cause irreversible damage.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

#### **4.3 Indication of any immediate medical attention and special treatment needed.**

Request immediate medical attention. Never administer anything orally to persons who are unconscious. Do not induce vomiting. If the person vomits, clear the respiratory tract. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

### SECTION 5: FIREFIGHTING MEASURES.

Flammable product, the necessary prevention measures should be taken in order to avoid risks, In case of fire, the following measures are recommended:

#### **5.1 Extinguishing media.**

##### **Suitable extinguishing media:**

Extinguisher powder or CO<sub>2</sub>. In case of more serious fires, also alcohol-resistant foam and water spray.

##### **Unsuitable extinguishing media:**

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

#### **5.2 Special hazards arising from the mixture.**

##### **Special risks.**

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Flammable vapors or gases.

#### **5.3 Advice for firefighters.**

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

#### **Fire protection equipment.**

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 23451-DECO-EPOXI 2C AGENTE CURADO 234 (B)



Version: 2  
Revision date: 12/06/2018

Page 4 of 12  
Print date: 12/06/2018

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

### SECTION 6: ACCIDENTAL RELEASE MEASURES.

#### 6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

#### 6.2 Environmental precautions.

Prevent the contamination of drains, surface or subterranean waters, and the ground.

#### 6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate decontaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

#### 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

### SECTION 7: HANDLING AND STORAGE.

#### 7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

#### 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):

Code	Description	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5.000	50.000

#### 7.3 Specific end use(s).

Not available.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 23451-DECO-EPOXI 2C AGENTE CURADO 234 (B)



Version: 2  
Revision date: 12/06/2018

Page 5 of 12  
Print date: 12/06/2018

### 8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m <sup>3</sup>
xylene	1330-20-7	United Kingdom [1]	Eight hours	500	221
			Short term	100	442
n-butanol, butan-1-ol	71-36-3	United Kingdom [1]	Eight hours		
			Short term	50	154
ethylbenzene	100-41-4	European Union [2]	Eight hours	100 (skin)	442 (skin)
			Short term	200 (skin)	884 (skin)
		United Kingdom [1]	Eight hours	100	441
			Short term	125	552

[1] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

[2] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
n-butanol, butan-1-ol CAS No: 71-36-3 EC No: 200-751-6	DNEL (Workers)	Inhalation, Long-term, Local effects	310 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Long-term, Local effects	55 (mg/m <sup>3</sup> )
	DNEL (General population)	Oral, Long-term, Systemic effects	3,125 (mg/kg bw/day)
ethylbenzene CAS No: 100-41-4 EC No: 202-849-4	DNEL (Workers)	Inhalation, Long-term, Systemic effects	77 (mg/m <sup>3</sup> )

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
n-butanol, butan-1-ol CAS No: 71-36-3 EC No: 200-751-6	aqua (freshwater)	0,082 (mg/L)
	aqua (marine water)	0,0082 (mg/L)
	aqua (intermittent releases)	2,25 (mg/L)
	PNEC STP	2476 (mg/L)
	sediment (freshwater)	0,178 (mg/kg sediment dw)
	sediment (marine water)	0,0178 (mg/kg sediment dw)
	soil	0,015 (mg/kg soil dw)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

### 8.2 Exposure controls.

#### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %
Uses:	The solvent coating for indoor use.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 23451-DECO-EPOXI 2C AGENTE CURADO 234 (B)



Version: 2  
Revision date: 12/06/2018

Page 6 of 12  
Print date: 12/06/2018

<b>Breathing protection:</b>			
If the recommended technical measures are observed, no individual protection equipment is necessary.			
<b>Hand protection:</b>			
PPE:	Work gloves.		
Characteristics:	«CE» marking, category I.		
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420		
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.		
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480
		Material thickness (mm):	0,35
<b>Eye protection:</b>			
PPE:	Protective goggles with built-in frame.		
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against splashing liquid, dust, smoke, fog and vapour.		
CEN standards:	EN 165, EN 166, EN 167, EN 168		
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.		
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.		
<b>Skin protection:</b>			
PPE:	Anti-static protective clothing.		
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.		
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5		
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.		
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.		
PPE:	Anti-static safety footwear.		
Characteristics:	«CE» marking, category II.		
CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346		
Maintenance:	The footwear should be checked regularly		
Observations:	The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.		

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

#### 9.1 Information on basic physical and chemical properties.

Appearance: Liquid with characteristic odour and colour

Colour: N.A./N.A.

Odour: Característico hidrocarburo

Odour threshold: N.A./N.A.

pH: N.A./N.A.

Melting point: N.A./N.A.

Boiling Point:  $\geq 130$  °C

Flash point:  $\geq 27$  °C

Evaporation rate: N.A./N.A.

Inflammability (solid, gas): N.A./N.A.

Lower Explosive Limit: N.A./N.A.

Upper Explosive Limit: N.A./N.A.

Vapour pressure: N.A./N.A.

Vapour density: N.A./N.A.

Relative density: 0.85-0.95

Solubility: N.A./N.A.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 23451-DECO-EPOXI 2C AGENTE CURADO 234 (B)



Version: 2  
Revision date: 12/06/2018

Page 7 of 12  
Print date: 12/06/2018

Liposolubility: N.A./N.A.  
Hydrosolubility: Immiscible  
Partition coefficient (n-octanol/water): N.A./N.A.  
Auto-ignition temperature: N.A./N.A.  
Decomposition temperature: N.A./N.A.  
Viscosity: 45-55 KU  
Explosive properties: N.A./N.A.  
Oxidizing properties: N.A./N.A.  
N.A./N.A.= Not Available/Not Applicable due to the nature of the product

### 9.2 Other information.

Pour point: N.A./N.A.  
Blink: N.A./N.A.  
Kinematic viscosity: N.A./N.A.  
N.A./N.A.= Not Available/Not Applicable due to the nature of the product

## SECTION 10: STABILITY AND REACTIVITY.

### 10.1 Reactivity.

If the storage conditions are satisfied, does not produce dangerous reactions.

### 10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

### 10.3 Possibility of hazardous reactions.

Flammable liquid and vapour.

### 10.4 Conditions to avoid.

Avoid the following conditions:

- High temperature.
- Static discharge.
- Contact with incompatible materials.
- Avoid temperatures near or above the flash point. Do not heat closed containers. Avoid direct sunlight and heat, as these may cause a risk of fire.

### 10.5 Incompatible materials.

Avoid the following materials:

- Explosives materials.
- Toxic materials.
- Oxidizing materials.

### 10.6 Hazardous decomposition products.

In case of fire, dangerous decomposition products can be generated, such as carbon monoxide and dioxide and nitrogen fumes and oxides.

## SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT PREPARATION. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

### 11.1 Information on toxicological effects.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

### Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	Test	Kind	Value
ethylbenzene	Oral	LD50	Rat	3500 mg/kg bw [1]

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 23451-DECO-EPOXI 2C AGENTE CURADO 234 (B)



Version: 2

Revision date: 12/06/2018

Page 8 of 12

Print date: 12/06/2018

CAS No: 100-41-4      EC No: 202-849-4		[1] AMA Archives of Industrial Health. Vol. 14, Pg. 387, 1956
	Dermal	LD50      Rabbit      15400 mg/kg bw [1]
	Inhalation	[1] Food and Cosmetics Toxicology. Vol. 13, Pg. 803, 1975

a) acute toxicity;

Not conclusive data for classification.

Acute Toxicity Estimate (ATE):

Mixtures:

ATE (Dermal) = 3.704 mg/kg

ATE (Oral) = 3.021 mg/kg

b) skin corrosion/irritation;

Product classified:

Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation;

Product classified:

Serious eye damage, Category 1: Causes serious eye damage.

d) respiratory or skin sensitisation;

Product classified:

Skin sensitiser, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Based on available data, the classification criteria are not met.

i) STOT-repeated exposure;

Based on available data, the classification criteria are not met.

j) aspiration hazard;

Based on available data, the classification criteria are not met.

### SECTION 12: ECOLOGICAL INFORMATION.

#### 12.1 Toxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value
ethylbenzene	Fish	LC50	Fish	80 mg/l (96 h) [1]
				[1] Mayer, F.L.Jr., and M.R. Ellersieck 1986. Manual of Acute Toxicity: Interpretation and Data Base for 410 Chemicals and 66 Species of Freshwater Animals. Resour.Publ.No.160, U.S.Dep.Interior, Fish Wildl.Serv., Washington, DC :505 p. (USGS Data File)

-Continued on next page.-



# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 23451-DECO-EPOXI 2C AGENTE CURADO 234 (B)



Version: 2

Revision date: 12/06/2018

Page 9 of 12

Print date: 12/06/2018

CAS No: 100-41-4      EC No: 202-849-4	Aquatic invertebrates	LC50      Crustacean      16,2 mg/l (48 h) [1] [1] MacLean, M.M., and K.G. Doe 1989. The Comparative Toxicity of Crude and Refined Oils to Daphnia magna and Artemia. Environment Canada, EE-111, Dartmouth, Nova Scotia :64 p
	Aquatic plants	EC50      Algae      5 mg/l (72 h) [1] [1] Galassi, S., M. Mingazzini, L. Vigano, D. Cesareo, and M.L. Tosato 1988. Approaches to Modeling Toxic Responses of Aquatic Organisms to Aromatic Hydrocarbons. Ecotoxicol.Environ.Saf. 16(2):158-169. Masten, L.W., R.L. Boeri, and J.D. Walker 1994. Strategies Employed to Determine the Acute Aquatic Toxicity of Ethyl Benzene, a Highly Volatile, Poorly Water-Soluble Chemical. Ecotoxicol.Environ.Saf. 27(3):335-348

### 12.2 Persistence and degradability.

There is no information available on the degradability of the substances present.

No information is available regarding the degradability of the substances present.No information is available about persistence and degradability of the product.

### 12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
n-butanol, butan-1-ol N. CAS: 71-36-3      EC No: 200-751-6	0,84	-	-	Very low
ethylbenzene N. CAS: 100-41-4      EC No: 202-849-4	3,15	-	-	Moderate

### 12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

### 12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

## SECTION 13 DISPOSAL CONSIDERATIONS.

### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 23451-DECO-EPOXI 2C AGENTE CURADO 234 (B)



Version: 2  
Revision date: 12/06/2018

Page 10 of 12  
Print date: 12/06/2018

### SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

**Land:** Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

**Sea:** Transport by ship: IMDG.

Transport documentation: Bill of lading

**Air:** Transport by plane: ICAO/IATA.

Transport document: Airway bill.

#### 14.1 UN number.

UN No: UN1263

#### 14.2 UN proper shipping name.

Description:

ADR: UN 1263, PAINT, 3, PG III, (E)

IMDG: UN 1263, PAINT, 3, PG III (27°C)

ICAO/IATA: UN 1263, PAINT, 3, PG III

#### 14.3 Transport hazard class(es).

Class(es): 3

#### 14.4 Packing group.

Packing group: III

#### 14.5 Environmental hazards.

Marine pollutant: No

#### 14.6 Special precautions for user.

Labels: 3



Hazard number: Not applicable.

ADR LQ: 5 L

IMDG LQ: 5 L

ICAO LQ: 10 L

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Transport by ship, FEm – Emergency sheets (F – Fire, S – Spills): F-E,S-E

Proceed in accordance with point 6.

#### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

The product is not transported in bulk.

### SECTION 15: REGULATORY INFORMATION.

#### 15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): P5c

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 23451-DECO-EPOXI 2C AGENTE CURADO 234 (B)



**Version: 2**  
**Revision date: 12/06/2018**

**Page 11 of 12**  
**Print date: 12/06/2018**

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

### 15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

### SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.(órganos de audición)

Classification codes:

Acute Tox. 4 : Acute toxicity (Dermal), Category 4  
Acute Tox. 4 : Acute toxicity (Inhalation), Category 4  
Acute Tox. 4 : Acute toxicity (Oral), Category 4  
Asp. Tox. 1 : Aspiration toxicity, Category 1  
Eye Dam. 1 : Serious eye damage, Category 1  
Eye Irrit. 2 : Eye irritation, Category 2  
Flam. Liq. 2 : Flammable liquid, Category 2  
Flam. Liq. 3 : Flammable liquid, Category 3  
Skin Irrit. 2 : Skin irritant, Category 2  
Skin Sens. 1 : Skin sensitiser, Category 1  
STOT RE 2 : Specific target organ toxicity following a repeated exposure, Category 2  
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

Sections changed compared with the previous version:

1,8,16

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
BCF: Bioconcentration factor.  
CEN: European Committee for Standardization.  
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.  
DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.  
EC50: Half maximal effective concentration.  
PPE: Personal protection equipment.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 23451-DECO-EPOXI 2C AGENTE CURADO 234 (B)



**Version: 2**

**Revision date: 12/06/2018**

**Page 12 of 12**

**Print date: 12/06/2018**

IATA: International Air Transport Association.  
ICAO: International Civil Aviation Organization.  
IMDG: International Maritime Code for Dangerous Goods.  
LC50: Lethal concentration, 50%.  
LD50: Lethal dose, 50%.  
Log Pow: Logarithm of the partition octanol-water.  
NOEC: No observed effect concentration.  
PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.  
RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.