



## TECHNICAL INFORMATION

### WALL-FIX

#### DESCRIPTION:

Odourless isolation paint for stains, WALL-FIX is odourless and fast drying. Time between coats is very short because of its fast drying time so it is recommend to be used in public areas such as offices, kitchens, hotels, public buildings, etc. Humidity and fungus resistant.

Features:

- ) Excellent adherence.
- ) Maximum coverage.
- ) Stable to yellowing.
- ) Good chemical resistance.
- ) Good covering power over satins of grease, nicotine, smoke, oil, etc.
- ) Excellent leveling and brushability.
- ) Odourless.
- ) No yellowing.

#### TECHNICAL DATA:

Fixed vehicle	Special resins.	
Colour	White.	
Gloss	Matt.	UNE-EN ISO 2813
Solids by weight	65 %	UNE-EN ISO 3251
Solids by volume	39 %	UNE 48090
Viscosity	118 – 124 KU (23 ± 2 °C)	UNE 48076
Specific weight	1.25 – 1.35 Kg./l (23 ± 2 °C)	UNE-EN ISO 2811-1
Theoretical spreading rate	10 – 12 m <sup>2</sup> /l and coat. Take in mind application leaking, surface irregularities, etc.	
Recommended thickness	80 – 100 microns wet; 32 – 40 microns dry per coat. Apply 2 coats as finish.	
Total drying	30 – 60 minutes.	UNE 48301
Repaint	4 – 6 hours.	
Solvent	Aliphatic hydrocarbons.	
Reaction to fire	Class M-1	UNE 23727
Reaction to fire	Bs1d0	UNE-EN 13501-1:2007

EU limit value for this product (cat. A/i): 500 g/l (2010). Max. content VOC: 400 g/l

#### APLICACION:

Isolate paint of smoke, grease, soot, stains of leaking water, suitable for restaurants, hotels, office, kitchens, etc.

#### Pinturas Decolor

Industrial Estate El Salvador Avenue 3<sup>a</sup>, Parcels 4 and 5

Apdo. 106 – 02630 La Roda (Albacete) Spain

Phone: +34 967 44 17 14

Fax: +34 967 44 33 54

E-mail: [dptotecnico@decolor.com](mailto:dptotecnico@decolor.com)

<http://www.decolor.com>



## TECHNICAL INFORMATION

### WALL-FIX

#### INSTRUCTIONS FOR USE:

Application methods: brush, roller or spray.  
Thinner and cleaning utensils: SOLVENT INODORO D.

Apply a first coat dilute with solvent INODORO D at 5 – 10%, for finishing apply one to two coats WALL-FIX non diluted.

Do not repaint with plastic paint or any other product not to reduce its isolating stains performance.

If you want to colour it can be used DECOLOR UNIVERSAL COLORANT, at most 5%.

In general we recommend:

- ) Apply between 5 °C and 35 °C.
- ) It is not recommended to apply in full sun or high temperatures of the surface.
- ) Perfectly mix the product before use.
- ) In case of contamination by fungus or algae:
  - Wash with a solution of water and bleach to 10%.
  - Rinse with water.
  - Let dry completely before beginning to paint.
  - Use products with protection against FUNGUS.
- ) In case of presence of saline efflorescence:
  - Brush and wash with hydrochloric acid diluted to 10% with water.
  - Rinse with water.
  - Let dry completely before beginning to paint.

#### PRESENTATION:

Metallic packaging of: 0.750 Litres; 4 Litres

#### STORAGE:

24 months in closed original container under roof and temperatures between 5 °C and 35 °C and protected from the weather.

#### ADDITIONAL INFORMATION:

The information contained in this document serves as a guide for the user but does not constitute a guarantee. For information about safety and the environment, please refer to the Safety Data Sheet.