

COATING

DECO-LITE HYDRO



Smooth finishing Hydro-Pliolite® revetment for decoration and protection of all types of surfaces of brickwork in general, combining a high grade of waterproofing with an excellent permeability to water vapour giving a high long life and durability.

Film-preserving paint that provides an excellent protection against a wide spectrum of fungi and algae.

- ✓ Water-repellent ISO 1062-3 W₃ (Low)
- ✓ Vapour permeable ISO 7783-2 V₁ (High)



GREATER DURABILITY OF THE FACADE:

- * The dirt on the facade is reduced.
- * Longer lasting color tones.
- * Reduction of efflorescence on the facade.
- * Reduction of the snail drool effect.

Properties

Smooth matt finishing revetment for decoration and protection of all types of interior and exterior surfaces of brickwork in general. Perfect for works where is required the highest performances of durability. It is enough waterproof to resist the penetration of rain water, and due to its nature micro porous and excellent adherence allow getting out the humidity that is inside the surface avoiding the blistering.

FACADE EN 1062-1

	Target	
EN 1062-3 (W)	W ₃ Low	≤ 0,1 kg/(m ² .h ^{0,5})
EN ISO 7783-2 (V)	V ₁ High	>150 g/(m ² .d) sd < 0,14 m
Ideal values		
	sd < 0,14 m	W ≤ 0.1 kg/(m ² .h ^{0,5})

