

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



22501-ALBOR SATIN 3-1 WHITE 100

Version 1 Date of compilation: 20/05/2024

Page 1 of 12
Print date: 20/05/2024

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: ALBOR SATIN 3-1 WHITE 100
Product Code: 22501
UFI: MT90-G228-H00R-YDJM

1.2 Relevant identified uses of the substance or mixture and uses advised against.

The solvent coating for interior and exterior use.

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **PINTURAS DECOLOR, S.L.**
Address: POL. INDUSTRIAL EL SALVADOR, AVENIDA 3ª, PARCELAS 4-5
City: 02630 - LA RODA
Province: ALBACETE - SPAIN
Telephone: +34 967 44 17 14
Fax: +34 967 44 33 54
E-mail: decolor@decolor.com
Web: www.decolor.com

1.4 Emergency telephone number: +34 967 44 17 14 (Only available during office hours; Monday-Friday; 09:00-18:00)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008:

Aquatic Chronic 3 : Harmful to aquatic life with long lasting effects.
Eye Irrit. 2 : Causes serious eye irritation.
Flam. Liq. 3 : Flammable liquid and vapour.
STOT SE 3 : May cause drowsiness or dizziness.
Skin Sens. 1 : May cause an allergic skin reaction.

2.2 Label elements.

Labelling in accordance with Regulation (EC) No 1272/2008:

Pictograms:



Signal Word:

Warning

Hazard statements:

H226 Flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



22501-ALBOR SATIN 3-1 WHITE 100

Version 1 Date of compilation: 20/05/2024

Page 2 of 12
Print date: 20/05/2024

Precautionary statements:

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P262	Do not get in eyes, on skin, or on clothing.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/...
P331	Do NOT induce vomiting.
P501	Dispose of contents/container in accordance with the applicable legislation on waste treatment.

EUH statements:

EUH066	Repeated exposure may cause skin dryness or cracking.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Contains:

Fatty acids, tall-oil, esters with polyethylene glycol mono(hydrogen maleate), compds. with amides from diethylenetriamine and tall-oil fatty acids
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

2.3 Other hazards.

The mixture does not contain substances classified as PBT.
The mixture does not contain substances classified as vPvB.
The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	Specifics concentration limits and Acute toxicity estimate
CAS No: 64742-48-9 Registration No: 01-2119463258-33-XXXX	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	20 - 25 %	Asp. Tox. 1, H304 - Flam. Liq. 3, H226 - STOT SE 3, H336	-
Index No: 607-337-00-8 CAS No: 125078-60-6 EC No: 406-052-4	di-tert-(C12-14)-alkylammonium 2-benzothiazolythiosuccinate	1 - 2.5 %	Acute Tox. 4 *, H302 - Aquatic Chronic 2, H411 - Eye Dam. 1, H318 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315	-

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



22501-ALBOR SATIN 3-1 WHITE 100

Version 1 Date of compilation: 20/05/2024

Page 3 of 12
Print date: 20/05/2024

CAS No: 222716-38-3	Fatty acids, tall-oil, esters with polyethylene glycol mono(hydrogen maleate), compds. with amides from diethylenetriamine and tall-oil fatty acids	1 - 2.5 %	Acute Tox. 4, H302 - Aquatic Acute 1, H400 (M=1) - Aquatic Chronic 1, H410 (M=1) - Eye Irrit. 2, H319 - STOT RE 2, H373 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-
Index No: 603-064-00-3 CAS No: 107-98-2 EC No: 203-539-1 Registration No: 01-2119457435-35	[1] 1-methoxy-2-propanol, monopropylene glycol methyl ether	0 - 20 %	Flam. Liq. 3, H226 - STOT SE 3, H336	-
CAS No: 34590-94-8 EC No: 252-104-2 Registration No: 01-2119450011-60-XXXX	[1] (2-methoxymethylethoxy)propanol	0 - 2.5 %	-	-

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

* See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a European Union exposure limit in the workplace (see section 8.1).

[2] Substance with a national workplace exposure limit (see section 8.1).

This mixture contains $\geq 1\%$ TiO₂ CAS 13463-67-7; EC 236-675-5. The Annex VI classification of titanium dioxide does not apply to this mixture according to its Note 10.

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Don't let the person to rub the affected eye.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



22501-ALBOR SATIN 3-1 WHITE 100

Version 1 Date of compilation: 20/05/2024

Page 4 of 12
Print date: 20/05/2024

SECTION 5: FIREFIGHTING MEASURES.

Flammable product, the necessary prevention measures should be taken in order to avoid risks, In case of fire, the following measures are recommended:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO₂. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Flammable vapors or gases.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



22501-ALBOR SATIN 3-1 WHITE 100

Version 1 Date of compilation: 20/05/2024

Page 5 of 12
Print date: 20/05/2024

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorized persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):

Code	Description	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5.000	50.000

7.3 Specific end use(s).

Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
1-methoxy-2-propanol, monopropylene glycol methyl ether	107-98-2	European Union [1]	Eight hours	100 (skin)	375 (skin)
			Short term	150 (skin)	568 (skin)
(2-methoxymethylethoxy)propanol	34590-94-8	European Union [1]	Eight hours	50 (skin)	308 (skin)
			Short term		

[1] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
1-methoxy-2-propanol, monopropylene glycol methyl ether CAS No: 107-98-2 EC No: 203-539-1	DNEL (Workers)	Inhalation, Chronic, Systemic effects	369 (mg/m ³)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

8.2 Exposure controls.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



22501-ALBOR SATIN 3-1 WHITE 100

Version 1 Date of compilation: 20/05/2024

Page 6 of 12
Print date: 20/05/2024

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %		
Uses:	The solvent coating for interior and exterior use.		
Breathing protection:			
If the recommended technical measures are observed, no individual protection equipment is necessary.			
Hand protection:			
PPE:	Work gloves.		
Characteristics:	«CE» marking, category I.		
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420		
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.		
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480
		Material thickness (mm):	0,35
Eye protection:			
PPE:	Face shield.		
Characteristics:	«CE» marking, category II. Face and eye protector against splashing liquid.		
CEN standards:	EN 165, EN 166, EN 167, EN 168		
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly.		
Observations:	Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame.		
Skin protection:			
PPE:	Anti-static protective clothing.		
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.		
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5		
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.		
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.		
PPE:	Anti-static safety footwear.		
Characteristics:	«CE» marking, category II.		
CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346		
Maintenance:	The footwear should be checked regularly		
Observations:	The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.		

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Physical state: Liquid

Colour: White

Odour: Característico hidrocarburo

Odour threshold: Not applicable/Not available due to the nature/properties of the product

Melting point: Not applicable/Not available due to the nature/properties of the product

Freezing point: Not applicable/Not available due to the nature/properties of the product

Boiling point or initial boiling point and boiling range: >=140 °C

Flammability: Not applicable/Not available due to the nature/properties of the product

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



22501-ALBOR SATIN 3-1 WHITE 100

Version 1 Date of compilation: 20/05/2024

Page 7 of 12
Print date: 20/05/2024

Lower explosion limit: Not applicable/Not available due to the nature/properties of the product
Upper explosion limit: Not applicable/Not available due to the nature/properties of the product
Flash point: ≥ 38 °C
Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product
Decomposition temperature: Not applicable/Not available due to the nature/properties of the product
pH: Not applicable (Substance/mixture is non-soluble (in water)).
Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product
Solubility: Not applicable/Not available due to the nature/properties of the product
Hydrosolubility: Immiscible
Liposolubility: Not applicable/Not available due to the nature/properties of the product
Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product
Vapour pressure: Not applicable/Not available due to the nature/properties of the product
Absolute density: Not applicable/Not available due to the nature/properties of the product
Relative density: 1.30-1.40
Relative vapour density: Not applicable/Not available due to the nature/properties of the product
Particle characteristics: Not applicable/Not available due to the nature/properties of the product

9.2 Other information

Information with regard to physical hazard classes

Flammable liquids:

Sustained combustibility: Yes.

Other safety characteristics

Viscosity: 75-85 KU

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

Flammable liquid and vapour.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. Splashes in the eyes can cause irritation.

IRRITANT MIXTURE. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

11.1 Information on hazard classes as defined in Regulation (EC) N° 1272/2008.

There are no tested data available on the product.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

a) acute toxicity;

Not conclusive data for classification.

Acute Toxicity Estimate (ATE):

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



22501-ALBOR SATIN 3-1 WHITE 100

Version 1 Date of compilation: 20/05/2024

Page 8 of 12
Print date: 20/05/2024

Mixtures:

ATE (Oral) = 24.390 mg/kg

b) skin corrosion/irritation;
Based on available data, the classification criteria are not met.

c) serious eye damage/irritation;
Product classified:
Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;
Product classified:
Skin sensitizer, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;
Not conclusive data for classification.

f) carcinogenicity;
Not conclusive data for classification.

g) reproductive toxicity;
Not conclusive data for classification.

h) STOT-single exposure;
Product classified:
Specific target organ toxicity following a single exposure, Category 3: May cause drowsiness or dizziness.

i) STOT-repeated exposure;
Based on available data, the classification criteria are not met.

j) aspiration hazard;
Based on available data, the classification criteria are not met.

11.2 Information on other hazards.

Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

Other information

There is no information available on other adverse health effects.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
1-methoxy-2-propanol, monopropylene glycol methyl ether CAS No: 107-98-2 EC No: 203-539-1	-0,44	-	-	Very low

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

22501-ALBOR SATIN 3-1 WHITE 100



Version 1 Date of compilation: 20/05/2024

Page 9 of 12
Print date: 20/05/2024

12.4 Mobility in soil.

No information is available about the mobility in soil.
The product must not be allowed to go into sewers or waterways.
Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

12.7 Other adverse effects.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.
No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.
Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG.

Transport documentation: Bill of lading

Air: Transport by plane: ICAO/IATA.

Transport document: Airway bill.

14.1 UN number or ID number.

UN No: UN1263

14.2 UN proper shipping name.

Description:

ADR/RID: UN 1263, PAINT, 3, PG III, (E)

IMDG: UN 1263, PAINT, 3, PG III (38°C)

ICAO/IATA: UN 1263, PAINT, 3, PG III

14.3 Transport hazard class(es).

Class(es): 3

14.4 Packing group.

Packing group: III

14.5 Environmental hazards.

Marine pollutant: No

Transport by ship, FEM – Emergency sheets (F – Fire, S - Spills): F-E, S-E

14.6 Special precautions for user.

Labels: 3

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



22501-ALBOR SATIN 3-1 WHITE 100

Version 1 Date of compilation: 20/05/2024

Page 10 of 12
Print date: 20/05/2024



Hazard number: Not applicable.

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Proceed in accordance with point 6.

ADR LQ: 5 L

IMDG LQ: 5 L

ICAO LQ: 10 L

14.7 Maritime transport in bulk according to IMO instruments.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Restrictions on the manufacturing, placing on the market and use of certain dangerous substances, mixtures and articles:

Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
3. Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: - ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, - tricks and jokes, - games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: - can be used as fuel in decorative oil lamps for supply to the general public, and, - present an aspiration hazard and are labelled with H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: (a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: 'Keep lamps filled with this liquid out of the reach of children'; and, by 1 December 2010, 'Just a sip of lamp oil - or even sucking the wick of lamps - may lead to life-threatening lung damage'; (b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



22501-ALBOR SATIN 3-1 WHITE 100

Version 1 Date of compilation: 20/05/2024

Page 11 of 12
Print date: 20/05/2024

	sip of grill lighter may lead to life threatening lung damage'; (c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
--	--

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Classification codes:

Acute Tox. 4 : Acute toxicity (Oral), Category 4
Aquatic Acute 1 : Acute toxicity to the aquatic environment, Category 1
Aquatic Chronic 1 : Chronic effect to the aquatic environment, Category 1
Aquatic Chronic 2 : Chronic effect to the aquatic environment, Category 2
Aquatic Chronic 3 : Chronic effect to the aquatic environment, Category 3
Asp. Tox. 1 : Aspiration toxicity, Category 1
Eye Dam. 1 : Serious eye damage, Category 1
Eye Irrit. 2 : Eye irritation, Category 2
Flam. Liq. 3 : Flammable liquid, Category 3
STOT RE 2 : Specific target organ toxicity following a repeated exposure, Category 2
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3
Skin Irrit. 2 : Skin irritant, Category 2
Skin Sens. 1 : Skin sensitiser, Category 1

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR:	Agreement concerning the International Carriage of Dangerous Goods by Road.
BCF:	Bioconcentration factor.
CEN:	European Committee for Standardization.
DMEL:	Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



22501-ALBOR SATIN 3-1 WHITE 100

Version 1 Date of compilation: 20/05/2024

Page 12 of 12
Print date: 20/05/2024

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
EC50: Half maximal effective concentration.
PPE: Personal protection equipment.
IATA: International Air Transport Association.
ICAO: International Civil Aviation Organization.
IMDG: International Maritime Code for Dangerous Goods.
LC50: Lethal concentration, 50%.
LD50: Lethal dose, 50%.
NOEC: No observed effect concentration.
RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2020/878.

Regulation (EC) No 1907/2006.

Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.