(in accordance with Regulation (EU) 2020/878)

24151-DECO-EPOXY-2C-LD-24151-B

Version 1 Date of compilation: 21/01/2019

Version 6 (replaces version 5) Revision date: 07/07/2025



Page 1 of 10

Print date: 07/07/2025

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: DECO-EPOXY-2C-LD-24151-B

Product Code: 24151

UFI: FGV4-K2X8-W009-EP22

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Coating for floors 2-component.

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: PINTURAS DECOLOR

Address: POL. INDUSTRIAL EL SALVADOR, AVENIDA 3ª, PARCELAS 4-5

 City:
 02630 - LA RODA

 Province:
 ALBACETE - SPAIN

 Telephone:
 +34 967 44 17 14

 Fax:
 +34 967 44 33 54

 E-mail:
 decolor@decolor.com

 Web:
 www.decolor.com

1.4 Emergency telephone number: +34 967 44 17 14 (Only available during office hours; Monday-Friday; 09:00-18:00)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008:

Acute Tox. 4 : Harmful if swallowed. Eye Dam. 1 : Causes serious eye damage.

Repr. 2: Suspected of damaging fertility or the unborn child. Skin Corr. 1A: Causes severe skin burns and eye damage. Skin Sens. 1: May cause an allergic skin reaction.

2.2 Label elements.

Labelling in accordance with Regulation (EC) No 1272/2008:

Pictograms:







Signal Word:

Danger

Hazard statements:

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H361d Suspected of damaging the unborn child.

Precautionary statements:

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash ... thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...

(in accordance with Regulation (EU) 2020/878)

24151-DECO-EPOXY-2C-LD-24151-B



Date of compilation: 21/01/2019 Version 1

Page 2 of 10 Version 6 (replaces version 5) Revision date: 07/07/2025 Print date: 07/07/2025

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or

shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor/... P321 Specific treatment (see ... on this label).

Contains: benzyl alcohol salicylic acid 3-aminomethyl-3,5,5-trimethylcyclohexylamine m-phenylenebis(methylamine)

2.3 Other hazards.

The mixture does not contain substances classified as PBT.

The mixture does not contain substances classified as vPvB.

The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	Specifics concentration limits and Acute toxicity estimate
Index No: 603-057- 00-5 CAS No: 100-51-6 EC No: 202-859-9 Registration No: 01- 2119492630-38-XXXX	benzyl alcohol	10 - 75 %	Acute Tox. 4, H302 - Eye Irrit. 2, H319 - Skin Sens. 1B, H317	Oral: ETA = 1200 mg/kg bw (ATP 21)
Index No: 612-067- 00-9 CAS No: 2855-13-2 EC No: 220-666-8 Registration No: 01- 2119514687-32-XXXX	3-aminomethyl-3,5,5-trimethylcyclohexylamine	5 - 25 %	Acute Tox. 4, H302 - Eye Dam. 1, H318 - Skin Corr. 1B, H314 - Skin Sens. 1A, H317	Skin Sens. 1A, H317: C ≥ 0,001 % Oral: ETA = 1030 mg/kg pc (ATP 17)
CAS No: 1477-55-0 EC No: 216-032-5 Registration No: 01- 2119480150-50-XXXX	m-phenylenebis(methylamine)	5 - 25 %	Acute Tox. 4, H302 - Aquatic Chronic 3, H412 - Skin Corr. 1A, H314 - Skin Sens. 1, H317	-
Index No: 607-732- 00-5 CAS No: 69-72-7 EC No: 200-712-3 Registration No: 01- 2119486984-17-XXXX	salicylic acid	3 - 10 %	Acute Tox. 4, H302 - Eye Dam. 1, H318 - Repr. 2, H361d	-

^(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

SECTION 4: FIRST AID MEASURES.

(in accordance with Regulation (EU) 2020/878)

24151-DECO-EPOXY-2C-LD-24151-B

21/01/2019 Page 3 of 10

INTURAS

Version 1 Date of compilation: 21/01/2019

Version 6 (replaces version 5) Revision date: 07/07/2025 Print date: 07/07/2025

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

Eye contact.

Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Dont let the person to rub the affected eye.

Skin contact

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners. The use of personal protective equipment is recommended for people providing first aid (see section 8).

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Corrosive Product, contact with eyes or skin can cause burns; ingestion or inhalation can cause internal damage, if this occurs immediate medical assistance is required.

Harmful Product, prolonged exposure due to inhalation may cause anaesthetic effects and the need for immediate medical assistance.

Long-term chronic exposure may result in injury to certain organs or tissues.

Contact with eyes may cause irreversible damage.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Keep the person comfortable. Turn him/her over to the left side and stay there while waiting for medical care.

SECTION 5: FIREFIGHTING MEASURES.

The product does not present any particular risk in case of fire.

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- NOx (nitrogen oxides).

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

(in accordance with Regulation (EU) 2020/878)

24151-DECO-EPOXY-2C-LD-24151-B

Version 1 Date of compilation: 21/01/2019

Version 6 (replaces version 5) Revision date: 07/07/2025



Page 4 of 10 Print date: 07/07/2025

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product not classified as hazardous for the environment, avoid spillage as much as possible.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

The product does NOT contain substances with Professional Exposure Environmental Limit Values. The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
benzyl alcohol	DNEL	Inhalation, Chronic, Systemic effects	90
CAS No: 100-51-6	(Workers)		(mg/m³)
EC No: 202-859-9	,		, ,

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %		
Uses:	Coating for floors 2-component.		
Breathing protection:			
PPE:	Filter mask for protection against gases and particles.		

(in accordance with Regulation (EU) 2020/878)

24151-DECO-EPOXY-2C-LD-24151-B

Date of compilation: 21/01/2019 **Version 1 Version 6 (replaces version 5)** Revision date: 07/07/2025



Page 5 of 10 Print date: 07/07/2025

«CE» marking, category III. The mask must have a wide field of vision and an Characteristics:

anatomically designed form in order to be sealed and watertight.

CEN standards: EN 136, EN 140, EN 405

Should not be stored in places exposed to high temperatures and damp environments before use. Special Maintenance:

attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.

Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach Observations: the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols:

P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.

Filter Type needed:

Hand protection:

Non-disposable protective gloves against chemicals. PPE:

«CE» marking, category III. Check the list of chemicals for which the glove has Characteristics:

been tested.

EN 374-1, En 374-2, EN 374-3, EN 420 CEN standards:

A schedule for the periodical replacement of gloves should be established in order to guarantee their Maintenance: replacement before pollutants permeate them. The use of contaminated gloves could be more dangerous

than not using gloves, since the pollutant can gradually accumulate in the glove's material.

They are to be replaced whenever tears, cracks or deformations are observed or when exterior dirt could

reduce their strength.

Breakthrough time Material thickness Material: PVC (polyvinyl chloride) > 480 0,35 (min.): (mm):

Eye protection:

Observations:

Observations:

Protective goggles with built-in frame. PPE:

«CE» marking, category II. Eye protector with built-in frame for protection against Characteristics:

dust, smoke, fog and vapour. CEN standards: EN 165, EN 166, EN 167, EN 168

Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should Maintenance:

be disinfected periodically following the manufacturer's instructions.

Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, Observations:

scraping etc. Skin protection:

PPE: Chemical protective clothing

«CE» marking, category III. Clothing should fit properly. The level of protection

Characteristics: must be set according to a test parameter called BT (Breakthrough Time), which

indicates how long it takes for the chemical to pass through the material.

CEN standards: EN 464,EN 340, EN 943-1, EN 943-2, EN ISO 6529, EN ISO 6530, EN 13034 In order to guarantee uniform protection, follow the washing and maintenance instructions provided by Maintenance:

the manufacturer.

The protective clothing's design should facilitate correct positioning, staying in place without moving for

the period of use expected, bearing in mind environmental factors as well as any movement or position

the user might adopt while carrying out the activity.

PPF. Anti-static safety footwear against chemicals.

«CE» marking, category III. Check the list of chemicals against which the footwear Characteristics:

is resistant.

EN ISO 13287, EN 13832-1, EN 13832-2, EN 13832-3, EN ISO 20344, EN ISO CFN standards:

20345

For correct maintenance of this kind of safety footwear, it is necessary to observe the instructions Maintenance:

specified by the manufacturer. The footwear should be replaced as soon as any sign of damage is

observed.

The footwear should be cleaned regularly and dried when damp, although it should not be placed too Observations:

close to a source of heat in order to avoid any sharp changes in temperature.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Physical state: Liquid Colour: Colourless

Odour: Not applicable/Not available due to the nature/properties of the product

Odour threshold: Not applicable/Not available due to the nature/properties of the product Melting point: Not applicable/Not available due to the nature/properties of the product Freezing point: Not applicable/Not available due to the nature/properties of the product

Boiling point or initial boiling point and boiling range: >200 °C

Flammability: Not applicable/Not available due to the nature/properties of the product Lower explosion limit: Not applicable/Not available due to the nature/properties of the product

(in accordance with Regulation (EU) 2020/878)

24151-DECO-EPOXY-2C-LD-24151-B

Version 1 Date of compilation: 21/01/2019

Version 6 (replaces version 5) Revision date: 07/07/2025



Page 6 of 10 Print date: 07/07/2025

Upper explosion limit: Not applicable/Not available due to the nature/properties of the product

Flash point: >100 °C

Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product Decomposition temperature: Not applicable/Not available due to the nature/properties of the product

pH: Not applicable (Substance/mixture is non-soluble (in water)).

Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product

Solubility: Not applicable/Not available due to the nature/properties of the product Hydrosolubility: Not applicable/Not available due to the nature/properties of the product Liposolubility: Not applicable/Not available due to the nature/properties of the product

Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product

Vapour pressure: Not applicable/Not available due to the nature/properties of the product Absolute density: Not applicable/Not available due to the nature/properties of the product

Relative density: 1.05

Relative vapour density: Not applicable/Not available due to the nature/properties of the product Particle characteristics: Not applicable/Not available due to the nature/properties of the product

9.2 Other information

Not applicable/Not available due to the nature/properties of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008.

There are no tested data available on the product.

Splashes in the eyes can cause serious and irreversible damage.

a) acute toxicity;

Product classified:

Acute toxicity (Oral), Category 4: Harmful if swallowed.

Acute Toxicity Estimate (ATE):

Mixtures:

ATE (Oral) = 500 mg/kg

b) skin corrosion/irritation;

Product classified:

Skin Corrosive, Category 1A: Causes severe skin burns and eye damage.

c) serious eye damage/irritation;

Product classified:

Serious eye damage, Category 1: Causes serious eye damage.

d) respiratory or skin sensitisation;

Product classified:

(in accordance with Regulation (EU) 2020/878)

24151-DECO-EPOXY-2C-LD-24151-B

Version 1 Date of compilation: 21/01/2019 Page 7 of 10
Version 6 (replaces version 5) Revision date: 07/07/2025 Print date: 07/07/2025

Skin sensitiser, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Product classified:

Reproductive toxicant, Category 2: Suspected of damaging fertility or the unborn child.

h) STOT-single exposure;

Not conclusive data for classification.

i) STOT-repeated exposure;

Not conclusive data for classification.

i) aspiration hazard:

Not conclusive data for classification.

11.2 Information on other hazards.

Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

Other information

There is no information available on other adverse health effects.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name		Bioaccumulation			
		Log Pow	BCF	NOECs	Level
benzyl alcohol		1,05	_	_	Very low
CAS No: 100-51-6	EC No: 202-859-9	1,05			VCI y IOW

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

12.7 Other adverse effects.

The product is not affected by the Regulation (EU) 2024/590 of the European Parliament and of the Council of 7 February 2024 on substances that deplete the ozone layer.

No information is available about other adverse effects for the environment.

(in accordance with Regulation (EU) 2020/878)

24151-DECO-EPOXY-2C-LD-24151-B

Version 1 Date of compilation: 21/01/2019

Version 6 (replaces version 5) Revision date: 07/07/2025



Page 8 of 10 Print date: 07/07/2025

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

<u>Sea</u>: Transport by ship: IMDG. Transport documentation: Bill of lading <u>Air</u>: Transport by plane: ICAO/IATA. Transport document: Airway bill.

14.1 UN number or ID number.

UN No: UN2735

14.2 UN proper shipping name.

Description:

ADR/RİD: UN 2735, AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE), 8, PG II, (E)

IMDG: UN 2735, AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE),

8, PG II

ICAO/IATA: UN 2735, AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS 3-AMINOMETHYL-3,5,5-

TRIMETHYLCYCLOHEXYLAMINE), 8, PG II

14.3 Transport hazard class(es).

Class(es): 8

14.4 Packing group.

Packing group: II

14.5 Environmental hazards.

Marine pollutant: No

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-A,S-B

14.6 Special precautions for user.

Labels: 8



Hazard number: 80

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Proceed in accordance with point 6. IMDG Code segregation group: 18 Alkalis

ADR LQ: 1 L IMDG LQ: 1 L ICAO LQ: 0,5 L

14.7 Maritime transport in bulk according to IMO instruments.

The product is not transported in bulk.

(in accordance with Regulation (EU) 2020/878)

24151-DECO-EPOXY-2C-LD-24151-B

Version 1 Date of compilation: 21/01/2019

Version 6 (replaces version 5) Revision date: 07/07/2025



Page 9 of 10 Print date: 07/07/2025

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child. H412 Harmful to aquatic life with long lasting effects.

Classification codes:

Acute Tox. 4: Acute toxicity (Oral), Category 4

Aquatic Chronic 3: Chronic effect to the aquatic environment, Category 3

Eye Dam. 1: Serious eye damage, Category 1 Eye Irrit. 2: Eye irritation, Category 2 Repr. 2: Reproductive toxicant, Category 2 Skin Corr. 1A: Skin Corrosive, Category 1A Skin Corr. 1B: Skin Corrosive, Category 1B Skin Sens. 1: Skin sensitiser, Category 1 Skin Sens. 1A: Skin sensitiser, Category 1A Skin Sens. 1B: Skin sensitiser, Category 1B

Changes regarding to the previous version:

- Change of the name of the product (SECTION 1.1).

- Change of the uses of the product (SECTION 1.2).

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data
Health hazards Calculation method
Environmental hazards Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

BCF: Bioconcentration factor.

CEN: European Committee for Standardization.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be

considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not

anticipated.

EC50: Half maximal effective concentration. PPE: Personal protection equipment.

(in accordance with Regulation (EU) 2020/878)

24151-DECO-EPOXY-2C-LD-24151-B

ECOLOR®

Page 10 of 10

Print date: 07/07/2025

Version 1 Date of compilation: 21/01/2019

Version 6 (replaces version 5) Revision date: 07/07/2025

IATA: International Air Transport Association. ICAO: International Civil Aviation Organization.

IMDG: International Maritime Code for Dangerous Goods.

LC50: Lethal concentration, 50%.

LD50: Lethal dose, 50%.

NOEC: No observed effect concentration.

RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data:

http://eur-lex.europa.eu/homepage.html

http://echa.europa.eu/ Regulation (EU) 2020/878. Regulation (EC) No 1907/2006.

Regulation (EC) No 1907/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.