



## TECHNICAL INFORMATION

### ABSTRACTO DECORATIVE COATINGS

#### DESCRIPTION:

ABSTRACTO is a matt interior decorative paint with fine particles delicately pearled, easy to apply in 2 layers.

With its wide range of colours, ABSTRACTO really fits in all types of interiors.

#### TECHNICAL DATA:

pH	8.0 – 10.0 (23 ± 2 °C)	UNE-EN ISO 787-9
Theoretical spreading rate	First layer BASE DECORATIVA: 8 m <sup>2</sup> /l. Consideration should be given to application losses, surface irregularities, etc. Termination ABSTRACTO: 1,2 Kg./10 m <sup>2</sup>	
Solvent	Water.	
Emissions in the indoor air	Class A+	French Legislation Decree No. 2011-321 of March 23, 2011

EU limit value for this product (cat. A/k): 100 g/l (2010). Max. content VOC: 30 g/l

#### APPLICATION:

Decorative coating for obtaining the effects.

#### INSTRUCTIONS FOR USE:

Application methods: Brush, roller and spatula.  
Thinner and cleaning of tools: Water.

##### 1. Substrate preparation

It can be used over any kind of support, painted surfaces, plaster, plasterboard walls, walls with plaster or cement plaster, etc.

Surfaces should be dry and free of dust, rust, grease, etc. and primed properly with SELLADORA, SELLADORA AQUA, DECOKRILL PENETRANTE, or DECOKRIL.

In areas with poor adherence (powdery walls, surfaces with little pore, etc.) Should be applied initially DECOKRIL PENETRANTE to increase the adherence.

It is generally recommended:

- ) Apply between 5 °C and 35 °C.
- ) It is not recommended to apply elevated temperatures support.

#### **Pinturas Decolor**

Industrial Estate El Salvador Avenue 3<sup>a</sup>, Parcels 4 and 5  
Apdo. 106 – 02630 La Roda (Albacete) Spain  
Phone: +34 967 44 17 14 Fax: +34 967 44 33 54  
E-mail: [dptotecnico@decolor.com](mailto:dptotecnico@decolor.com) <http://www.decolor.com>



## TECHNICAL INFORMATION

### ABSTRACTO DECORATIVE COATINGS

---

) Perfectly homogenize the product before use.

#### **2. Application**

Perfectly homogenize the product before use.

Apply the first tinted coat BASE DECORATIVA, on properly prepared walls, with a roller of short hair paint to  $\pm 8 \text{ m}^2/\text{l}$ .

#### **3. Finishing**

When the first layer is dry (12 hours), apply with a flat brush ABSTRACTO with a spreading rate of  $\pm 120 \text{ g/m}^2$  with regular crossing movements and a regular touch.

When the finish begins to dry (5 to 10 min), smooth the ABSTRACTO finish with a soft plastic spatula to highlight the unique finish of the product.

#### PRESENTATION:

Plastic packaging of: 1 L.

#### STORAGE:

12-24 months in closed original container under roof and temperatures between 5 °C and 35 °C and protected from the weather.

#### ADDITIONAL INFORMATION:

The information contained in this document serves as a guide for the user but does not constitute a guarantee. For information about safety and the environment, please refer to the Safety Data Sheet.