TECHNICAL INFORMATION

CLASSIC TEAK OIL

DESCRIPTION

Mixture of natural oils and resins, to care for and beauty wood. Suitable for unvarnished wood, including exotic and tropical ones.

Features:

- The treated wood regains its natural balance and its original qualities of gloss, texture and colour. Sanding is not necessary for repainting.
- It restores the natural oils that wood loses over time.
- The wood is protected from stains and dust.
- Protects against fungi and bacteria.
- Brings out the natural grain of the wood.
- Does not cause wood peeling.
- Does not form a film, does not peel or crack.
- Fast drying.
- Withstands strong climatic changes, indoors and outdoors.

TECHNICAL DATA

Nature	Natural oils and resins.	
Colour	Colourless.	
Solids by weight	35 %	UNE-EN ISO 3251
Specific weight	0.80 – 0.90 kg/l (23 ± 2 ºC)	UNE-EN ISO 2811-1
Theoretical spreading rate	12 – 18 m^2/l and coat. Take in mind application leaking, surface irregularities, etc.	
Total drying	4 – 6 hours at 23 °C and 55% relative humidity. Depend on air temperature and ventilation.	UNE 48301
Repaint	12 – 24 hours.	
Solvent	Aliphatic hydrocarbons.	

EU limit value for this product (cat. A/f): 700 g/l (2010). Max. content VOC: 550 g/l

APLICATION

Maintenance and renovation of woods, especially teak, exotic and tropical woods without varnish. Especially suitable for outdoor furniture, floors and wooden structures. Can also be used indoors.

INSTRUCTIONS FOR USE

Application methods: brush, roller or spray.
Cleaning utensils: SYNTHETIC AND FATTY SOLVENT.

Pinturas Decolor
Industrial Estate El Salvador Avenue 3ª, Parcels 4 and 5
02630 La Roda (Albacete) Spain
Phone: +34 967 44 17 14
E-mail: dptotecnico@decolor.com http://www.decolor.com

TECHNICAL INFORMATION

CLASSIC TEAK OIL

Painted surfaces must be dry and clean of dust, rust, grease, etc.

The wood highly resinous must be cleaned previously with SYNTHETIC AND FATTY SOLVENT, UNIVERSAL SOLVENT or ODOURLESS SOLVENT, to avoid problems during the drying.

- Unpainted surfaces:
  - Wood in general: Apply 1-2 coats with an interval of 12-24 hours between coats.
- Painted surfaces:
  - Remove paint and varnish by polishing or sanding until complete elimination. After that proceed as unpainted surfaces.

In general, we recommend:

- Apply between 5 °C and 35 °C.
- It is not recommended to apply in full sun or high temperatures of the surface.
- Perfectly mix the product before use.

PRESENTATION

Metallic packaging of: 750 ml; 4 L

STORAGE

24 months in closed original container under roof and temperatures between 5 °C and 35 °C and protected from the weather.

ADDITIONAL INFORMATION

The information contained in this document serves as a guide for the user but does not constitute a guarantee. For information about safety and the environment, please refer to the Safety Data Sheet.

Pinturas Decolor
Industrial Estate El Salvador Avenue 3ª, Parcels 4 and 5
02630 La Roda (Albacete) Spain
Phone: +34 967 44 17 14
E-mail: dptotecnico@decolor.com http://www.decolor.com