



TECHNICAL INFORMATION

UNIVERSAL DECOTINT



DESCRIPTION

Universal colorant high concentrated with a high tinting power for tinting systems.

Features:

-  High colorant power.
-  High compatibility with water base and solvent base products.
-  All UNIVERSAL DECOTINT colorants are VOC and APEO free, meeting the latest environmental requirements.
-  Tinting systems DECO-COLOR.

TECHNICAL DATA

Name	Colour	Specific weight (Kg./l)	Light fastness of pigment. Full (1-8)	Light fastness of pigment. Reduced (1-8)	Weather resistance of pigment. Full (1-5)	Weather resistance of pigment. Reduced (1-5)	Heat fastness of pigment. (°C)
DKU	White P. WHITE 6	1.90	8	n/a	5	n/a	200
DMS	Yellow P. YELLOW 128	1.30	7-8	7-8	4-5	4	200
DQS	Yellow P. YELLOW 74	1.34	7-8	6-7	4-5	3	140
DTS	Yellow Oxide P. YELLOW 42	1.82	8	8	5	5	180
DUS	Orange P. ORANGE 73	1.36	8	6-7	4-5	3	200
DNS	Red P. RED 166	1.34	8	6-7	5	3-4	200
DVS	Red P. RED 112	1.25	8	6	4-5	3	180
DYS	Red Oxide P. RED 101	1.95	8	8	5	5	200
DBS	Magenta P. RED 122	1.13	7	7-8	4	4-5	200
DZS	Violet P. VIOLET 23	1.41	8	8	5	4	160
DLS	Blue P. BLUE 15:1	1.38	8	8	5	4-5	200
DRS	Blue P. BLUE 15:3	1.29	8	8	5	4-5	200
DPS	Green P. GREEN 7	1.39	8	8	5	4-5	200
DWS	Umber PR 101, PY 42, PBK 7	1.52	8	8	5	5	180
DXS	Black P. BLACK 7	1.42	8	8	5	5	200
DJS	Black P. BLACK 7	1.23	8	8	5	5	200

Pinturas Decolor

Industrial Estate El Salvador Avenue 3ª, Parcels 4 and 5

02630 La Roda (Albacete) Spain

Phone: +34 967 44 17 14

E-mail: dptotecnico@decolor.com

<http://www.decolor.com>



TECHNICAL INFORMATION

UNIVERSAL DECOTINT



APPLICATION

Universal colorant for tinting systems. Can be used with solvent or water based products.

INSTRUCTIONS FOR USE

Cleaning utensils: Water.

Homogenise well before usage, either by manual stirring or using automatic mixing equipment.

PRESENTATION

Plastic packaging of: 1 L

STORAGE

12 months in closed original container under roof and temperatures between 5 °C and 35 °C and protected from the weather.

ADDITIONAL INFORMATION

The information contained in this document serves as a guide for the user but does not constitute a guarantee. For information about safety and the environment, please refer to the Safety Data Sheet.

Pinturas Decolor

Industrial Estate El Salvador Avenue 3^a, Parcels 4 and 5

02630 La Roda (Albacete) Spain

Phone: +34 967 44 17 14

E-mail: dptotecnico@decolor.com

<http://www.decolor.com>