



TECHNICAL INFORMATION

REFLEJO DE ARENA DECORATIVE COATINGS

DESCRIPTION:

REFLEJO DE ARENA is an interior decorative painting that is applied on a first coat dyed.

REFLEJO DE ARENA is a sophisticated blend of natural river and pearl sand, a fine granite decoration at the same time matte and satiny that depends on the angle of reflection of the light.

REFLEJO DE ARENA is easy to apply, very resistant and adapts perfectly to a modern design and environment.

TECHNICAL DATA:

pH	8.0 – 10.0 (23 ± 2 °C)	UNE-EN ISO 787-9
Theoretical spreading rate	First layer BASE DECORATIVA: 8 m ² /l. Consideration should be given to application losses, surface irregularities, etc. Termination REFLEJO DE ARENA: 1,2 Kg./10 m ²	
Solvent	Water.	
Emissions in the indoor air	Class A+	French Legislation Decree No. 2011-321 of March 23, 2011

EU limit value for this product (cat. A/k): 100 g/l (2010). Max. content VOC: 30 g/l

APPLICATION:

Decorative coating for obtaining the effects.

INSTRUCTIONS FOR USE:

Application methods: Brush, roller and spatula.
Thinner and cleaning of tools: Water.

1. Substrate preparation

It can be used over any kind of support, painted surfaces, plaster, plasterboard walls, walls with plaster or cement plaster, etc.

Surfaces should be dry and free of dust, rust, grease, etc. and primed properly with SELLADORA, SELLADORA AQUA, DECOKRILL PENETRANTE, or DECOKRIL.

In areas with poor adherence (powdery walls, surfaces with little pore, etc.) Should be applied initially DECOKRIL PENETRANTE to increase the adherence.

It is generally recommended:



TECHNICAL INFORMATION

REFLEJO DE ARENA DECORATIVE COATINGS

-) Apply between 5 °C and 35 °C.
-) It is not recommended to apply elevated temperatures support.
-) Perfectly homogenize the product before use.

2. Application

Perfectly homogenize the product before use.

Apply the first coat stained BASE DECORATIVA, on properly prepared walls, with a roller of short hair paint to $\pm 8\text{m}^2/\text{l}$.

3. Finishing

When the first layer is dry (12 hours), apply with a flat brush the REFLEJO DE ARENA finish with regular crossing movements and a regular touch in sections of 1 m².

After dry, remove the REFLEJO DE ARENA layer with a slightly damp sponge.

It is recommended to complete the complete application of a wall.

PRESENTATION:

Plastic packaging of: 1 L.

STORAGE:

12-24 months in closed original container under roof and temperatures between 5 °C and 35 °C and protected from the weather.

ADDITIONAL INFORMATION:

The information contained in this document serves as a guide for the user but does not constitute a guarantee. For information about safety and the environment, please refer to the Safety Data Sheet.