



TECHNICAL INFORMATION

DECOPLAST ANTI-FISSURES



DESCRIPTION:

Elastic waterproofing mastic with fibres for the specific treatment of cracks and fissures.

Characteristics:

-) Elastic and waterproof.
-) Excellent open time.
-) Easy application.
-) High hardness and adhesion.
-) High filling power.
-) Exterior – Interior use.

TECHNICAL DATA:

Colour	White.	
Specific weight	1.60 – 1.70 Kg./l (23 ± 2 °C)	UNE-EN ISO 2811-1
pH	> 8.5 (23 ± 2 °C)	UNE-EN ISO 787-9
Theoretical spreading rate	1.70 – 1.80 Kg./m ² /1 mm. Take in mind application leaking, surface irregularities, etc.	
Reaction to fire	A2 - s1 - d0 Combustible.	UNE-EN 13501-1:2007
Total drying	Layer of 1 mm: 6 – 8 hours	UNE 48301
Repaint	24 hours	
Solvent	Water.	

EU limit value for this product (cat. A/c): 40 g/l (2010). Max. content VOC: 35 g/l

APPLICATION:

Putty ready for special use for crack repair, joint sealing, hole filling.

INSTRUCTIONS FOR USE:

Application methods: trowel or spatula.

Cleaning utensils: Water.

Ready for use.

Surfaces must be dry and clean of dirty, dust, grease, etc.

Clean cracks before coating by removing dust, poorly adhered foreign material or in poor condition or other undesirable elements on the support using a brush.

Pinturas Decolor

Industrial Estate El Salvador Avenue 3ª, Parcels 4 and 5

Apdo. 106 – 02630 La Roda (Albacete) Spain

Phone: +34 967 44 17 14

Fax: +34 967 44 33 54

E-mail: dptotecnico@decolor.com

<http://www.decolor.com>



TECHNICAL INFORMATION

DECOPLAST ANTI-FISSURES



Before coating, apply the right primer.

In general, we recommend:

-) Apply between 5 °C and 35 °C.
-) It is not recommended to apply in full sun or high temperatures of the surface.
-) Perfectly mix the product before use.

PRESENTATION:

Plastic packaging of: 1 Kg.; 5 Kg.

STORAGE:

12 months in closed original container under roof and temperatures between 5 °C and 35 °C and protected from the weather.

ADDITIONAL INFORMATION:

The information contained in this document serves as a guide for the user but does not constitute a guarantee. For information about safety and the environment, please refer to the Safety Data Sheet.